



# PFC Corofil Ablative Coating

## Application

PFC Corofil Ablative Coating is used to reinstate the fire resistant properties of PFC Corofil Coated Panels when installed around service penetrations in walls and floors. The ablative nature of the coating resists flame spread and helps prevent the passage of smoke between fire rated compartments.

## General Benefits:

- Designed for use with Corofil Coated Panel system
- Dries to give a sound, flexible white surface finish
- Easy to use fibre free coating

## Description

PFC Corofil Ablative Coating is a water based acrylic flexible coating which may be brush or spray applied to PFC Corofil Coated Panel System.

<b>Description</b>	Water based acrylic flexible coating
<b>Cure Rate</b>	0.5mm per day at 50% relative humidity 23°C
<b>Tack Free</b>	6 hours at 50% relative humidity 23°C
<b>Colour</b>	White
<b>Specific Gravity</b>	1.2 - 1.3 g/cm <sup>3</sup>
<b>Flashpoint</b>	None
<b>Application Temp Range</b>	+0°C to +30°C
<b>Remains Flexible Between</b>	-5°C to +70°C
<b>Shelf Life</b>	Up to 12 months when stored in unopened containers under cool dry conditions. AVOID FROST and extremes of temperature.

## TECHNICAL INFORMATION

Tested to **EN1366-3**  
**EN1366-4**

Available from our technical sales office. Email [tech@pfc-corofil.com](mailto:tech@pfc-corofil.com) for:

- Method Statement MSCOAT
- Safety Data Sheet SDCOAT



Certificate number: **FS453/03**

## ORDERING

Please order from our technical sales office.

PFC Corofil  
Units 3-4 King George Trading Estate  
Davis Road  
Chessington  
Surrey KT9 1TT

Tel: + 44 (0) 208 391 0533  
Fax: + 44 (0) 208 391 2723  
Email: [sales@pfc-corofil.co.uk](mailto:sales@pfc-corofil.co.uk)  
[www.pfc-corofil.co.uk](http://www.pfc-corofil.co.uk)

