PFC COROFIL
PASSIVE FIRE PROTECTION SOLUTIONS

Linear Gap Seals

Butyl Tape

Application

PFC Corofil Butyl Tape is a pre-formed, polyisobutylene (PIB) based sealing tape.

The strip can be used to seal dry wall track where they interface with construction soffits and floors

Product Data

Colour	White
Dimensions	3mm thick x 25mm wide x 3.6 linear metres long
Shelf Life	18 months in ambient conditions
Service Temperature Range	-40°C to +90°C
Joint Movement	Up to 15%

TECHNICAL INFORMATION

Available from our technical sales office.

Email tech@pfc-corofil.com for:

• Safety Data Sheet (SDBUTYL)

• Installation Instructions (MSBUTYL)

nsPlus

K10 15 / K10 25 / K10 30
K10 35 / K10 41 / K10 45 / K10 50
K10 115 / K10 125 / K10 145 / K10 155
K10 165 / K10 185 / K10 205 / K10 215

Please order from our technical sales office.

PFC Corofil
Units 3-4
King George Trading Estate
Davis Road
Chessington
Surrey KT9 1TT

Tel: + 44 (0) 208 391 0533
Fax: + 44 (0) 208 391 2723
Email: sales@pfc-corofil.com
www.pfc-corofil.com

nqa ISO 9001 Registered Quality Management

ASFP

This data sheet shows the only applications the product has been tested in. Please ensure the product has been tested in, and is suitable for your application (see PFC Corofil terms and conditions 13.1.1).

Doc Reference				TDBUTYL				
PB	SE	CB	CI	AB				
This Copy				Review Date				
May 2018				May 2020				