



PFC Corofil Fastight Coating



Description

PFC Corofil Fastight Coating is an easily applied water based permanently flexible acrylic for use with Corofil C144 Linear Gap Seals, C450 Cavity Firestop and C470 Raised Floor Firestop. The coating can be brush or spray applied.

General Benefits:

- Improved acoustic performance
- Improved air tightness
- Cold smoke seal
- Factory or site applied
- Also available as a 2 strip system with C144

Technical Data

Description	Water Based Acrylic Flexible Coating
Coating Thickness	1mm Dry Film Thickness (DFT)
Coverage	2.2 litres per m2
Application Temperature Range	+ 0°C + 30°C
Shelf Life	Up to 12 months when stored in unopened tubs under cool dry conditions. AVOID extremes of temperature

TECHNICAL INFORMATION

Available from our technical sales office.

Email tech@pfc-corofil.com for:

- Safety Data Sheet (SDFAST)
- Installation Instructions (MSFAST)

ORDERING

Please order from our technical sales office.

PFC Corofil
Units 3-4
King George Trading Estate
Davis Road
Chessington
Surrey KT9 1TT

Tel: + 44 (0) 208 391 0533
Fax: + 44 (0) 208 391 2723
Email: sales@pfc-corofil.com
www.pfc-corofil.com

