

04 | K Mix Damp Resistant Plaster is a renovation plaster used to control salt migration and dampness in walls.



Plastering

K Mix Damp Resistant plaster is designed for internal use to control salt migration and allow walls to dry.

Coverage:

Approx. 1.25kg / mm thick / m²

Approx. 25kg / m²

Nominal 20mm thickness

23kg bags

Appearance: off-white in colour

Packaging: 23kg bags

Compressive Strength: CS II

Adhesion: > 0.2 N/mm²

Thermal Conductivity: 0.31 W/mK

Reaction to fire: Class A1

Water Vapour Permeability: $\mu \leq 15$

Dry Bulk Density: 1100 kg / m³

Water Absorption: > 0.3 kg / m² (after 24hr)



Internal Plastering

Overview

K Mix Damp Resistant Plaster is designed to be applied to salt contaminated walls following the installation of a damp proof course and has a porous structure to allow walls to dry out by evaporation. K Mix Damp Resistant Plaster is normally applied in two coats as a backing for skim and paint finishes and requires only the addition of water and 10 minutes mixing time prior to use.

Quality Assured
Manufacturing Process
BS EN ISO 9001:2015

Key Features

- ▶ Breathable internal plaster
- ▶ Suitable for use on salt and damp contaminated walls
- ▶ Workable and easy to use
- ▶ Allows walls to dry naturally

