



## **K Pro**

### **Protective Treatment For Render**

K Pro is a water based protective treatment used to provide long term, enhanced water repellent properties to external render and other masonry surfaces.

- ✓ Enhanced water repellency
- ✓ Helps combat problems associated with water intrusion
- ✓ Enables the substrate to breathe
- ✓ Keeps substrate clean & dry for longer

## Appearance

- Form: milky / opaque, free flowing liquid (clear when fully dry)
- Density: 1.0 (approximately)
- pH: 7 (approximately)

## Preparation

- It is recommended that a trial on an inconspicuous area is first carried out to ensure suitability of the product and final appearance of the treated surface
- The surface to be treated should be clean and free from any loose or friable material, including algae
- For best results apply onto a dry background
- For optimum effectiveness substrate must be totally dry to allow deep penetration

## Application

- Stir or shake before use
- Can be applied by roller, painting, flooding or airless spraying
- Application rate: approximately 5 sq. metres per litre per coat, depending on the absorbency of the surface to be treated
- For optimum protection a second coat should be applied
- Water and oil resistance develops within 24 hours of application

## Cleaning

- Rinse tools and equipment with water

## Packaging

- K Pro is packed in 25 Litre screw cap plastic containers
- The shelf life is approximately 6 months if stored off ground in original, sealed containers and protected against frost and away from direct sunlight

## Safety

- K Pro is non flammable
- Please refer to the separate Material Safety Data Sheet

