

New Mineral TC is an easy to use, reliable cement based, polymer modified, self-coloured mineral thin coat render.

- Faster drying times at lower temperatures and high humidity
- Available in 2 textures (Mineral TC 2 & Mineral TC 4) and 4 standard colours
- Primarily for external render, can be used internally
- Requires only the addition of water and 10 minutes mixing time



Scan for info









Pure White Granite Pearl



## Application

- Apply fresh basecoat a minimum of 14 days before work commences
- Prime walls using K Rend Primer TC, colour co-ordinated to topcoat and allow 24 hours to dry before applying topcoat
- Add 5 6 litres of water per 25kg sack
- Mix thoroughly for 10 minutes
- Apply the product to the thickness of the largest grain size using a stainless steel float and allow to take up slightly
- Rub the surface in circular motions using a plastic float to create texture

# Preparation

- A test panel to check colour and final appearance is recommended
- It is recommended that a K Rend basecoat is applied as a background for K Rend Mineral TC
- Backgrounds should be clean, level, dry and free from efflorescence
- Mask all adjacent surfaces including windows, sills, doors, timber, glass, brick & flooring
- Protect weather exposed surfaces

### Colour

Available in two textures and in 4 standard colours

# Coverage

Mineral TC 2: 2 - 2.5 kg / sq m approx.

Mineral TC 4: 4.5 - 5 kg / sq m approx.

# Kitemark Classifications

Compressive Strenght: CSIII

Capillary Water Absorption: W2

## Sales & Technical Support:

Technical advice & product specifications are available from our Technical Support Centre on:

Tel: 028 2826 0766 Sales@K-Rend.co.uk www.K-Rend.co.uk











