

S10 Bonding Primer *High Adhesion*



Technical Data

Pack Size
25L Jerry-can

Application Tool
Brush, Roller or Spray

Suitable Substrate
Concrete, Clay, Lightweight
Block and Brick

Dilution Rate
Apply Neat

Coverage
Approx. 5m² per litre

Humidity Requirement
Less than 85%

Application Temperature
3°C - 25°C for a minimum of
24 hours



Highly Vapour
Permeable



High Adhesion



Roller, Brush or
Spray Application



Ready to Use



Silicone
Technology



Water Based

DESCRIPTION

Ecorend S10 Bonding Primer is a silicone resin based primer, specifically designed for use on masonry substrates. The fine particle size polymers within the product ensure deep penetration into the substrate, creating ultra high adhesion, whilst the silicone resin ensures that the primer matches the breathability of its subsequent topcoats.

PREPARATION

New build - Remove all loose and flaking material from the substrate, (typically mortar snots or site contamination and algae growth). This should be removed with a power wash and by cleaning the surface with a hard bristle brush.

APPLICATION

Ecorend S10 Bonding Primer is applied neat as instructed above with a roller, brush or spray.

STORAGE

When stored unopened in a dry place at temperatures above 5°C, shelf life is 12 months from date of manufacture.

TOOL CLEANING

All equipment must be washed with clean water immediately after use. Waste material should not be emptied into drainage systems.

HEALTH & SAFETY INSTRUCTIONS

This product contains a biocide for the protection of the cured product. Contains 2-OTYL-2H-ISOTHIAZOL-3-ONE. May produce an allergic reaction. For further information, please request the material safety data sheet for this product.

IMPORTANT INFORMATION

DO NOT apply if frost is forecast within 24 hours, in wet conditions, in temperatures below 3°C or above 25°C, to elevations in direct sunlight or to substrates that are hot. Coverage rates are approx. and do not take into account wastage and uneven substrates.